





> gentle on joints, no stumbling edge







# Softbed LongLine

## continuous roll system in 2 layers



## | THICKNESS


ca. 5 cm

| 2-LAYER COMPOSITION

| COMFORT









### | 2-layer composition

> seamless and permanent softness for every load condition

#### | Foam-supported, jointless softness within the roll edges

- > supports the correct resting position of the cow
- > improves slip resistance

#### | Smart roll design

- > integrated sealing lips and dirt barriers minimize soiling and protect the foam
- > trapezoidal strut sections over the foam area improve stability and durability
- > prefabricated, countersunk fixing points at the head edge ease installation

#### | Proven, easy to maintain pebbled surface

#### | Rear area

- > pronounced slope: promotes quick drying off of the surface
- > chamfer: gentle on animal joints, no stumbling edge

#### | Installation independent of divider arrangement

#### **DIMENSIONS**

	THICKNESS	WIDTH	LENGTH
Softbed LongLine	ca. 5 cm		
consists of:			
Softbed LongLine (top covering)	17 mm	180 cm	2.5 - 35 m in 10-cm increments
KRAI-PUR (foam)	33 mm	140 cm	200 cm

#### Side closure bars

WELA-R/WS-R 170 (right) and WELA-L/WS-L 170 (left) WIDTH: 9 cm, LENGTH: 170 cm

#### **ACCESSORIES**

**Middle bar** WELA-M/WS-M 170 for connecting two rolls

**WIDTH:** 13 cm, **LENGTH:** 170 cm

## INSTALLATION

fixing with 2 - 3 framing plugs / cubicle at the head edge, with 6 - 8 framing plugs at the bars

## Your KRAIBURG dealer:



Please take notice of the corresponding KRAIBURG specifications and installation instructions with useful advice and tips. You will obtain these at your local KRAIBURG dealer or at www.kraiburg-elastik.com.



The products presented here should only be used for the mentioned applications. Technical specifications are subject to alterations. Tolerances see www.kraiburg-elastik.com. All sales are subject to our General Terms and Conditions. Legal basis is the German version of the document.